



SIMATIC S7-300, CPU 312C Compact CPU with MPI, 10 DI/6 DQ, 2 high-speed counters (10 kHz) Integr. power supply 24 V DC, work memory 64 KB, Front connector (1x 40-pole) and Micro Memory Card required

General information	
HW functional status	01
Firmware version	V3.3
Engineering with	
<ul style="list-style-type: none"> Programming package 	STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
external protection for power supply lines (recommendation)	Miniature circuit breaker, type C; min. 2 A; miniature circuit breaker type B, min. 4 A
Mains buffering	
<ul style="list-style-type: none"> Mains/voltage failure stored energy time Repeat rate, min. 	5 ms 1 s
Load voltage L+	
Digital outputs	
— Rated value (DC)	24 V
— Reverse polarity protection	No
Input current	
Current consumption (rated value)	570 mA
Current consumption (in no-load operation), typ.	90 mA
Inrush current, typ.	5 A
I ² t	0.7 A ² ·s
Digital outputs	
<ul style="list-style-type: none"> from load voltage L+, max. 	25 mA
Power loss	
Power loss, typ.	8 W
Memory	
Work memory	
<ul style="list-style-type: none"> integrated expandable 	64 kbyte No
Load memory	
<ul style="list-style-type: none"> Plug-in (MMC) Plug-in (MMC), max. Data management on MMC (after last programming), min. 	Yes 8 Mbyte 10 a
Backup	
<ul style="list-style-type: none"> present without battery 	Yes; Guaranteed by MMC (maintenance-free) Yes; Program and data
CPU processing times	

for bit operations, typ.	0.1 µs
for word operations, typ.	0.24 µs
for fixed point arithmetic, typ.	0.32 µs
for floating point arithmetic, typ.	1.1 µs

CPU-blocks

Number of blocks (total)	1 024; (DBs, FCs, FBs); the maximum number of loadable blocks can be reduced by the MMC used.
--------------------------	---

DB

<ul style="list-style-type: none"> • Number, max. • Size, max. 	1 024; Number range: 1 to 16000 64 kbyte
--	---

FB

<ul style="list-style-type: none"> • Number, max. • Size, max. 	1 024; Number range: 0 to 7999 64 kbyte
--	--

FC

<ul style="list-style-type: none"> • Number, max. • Size, max. 	1 024; Number range: 0 to 7999 64 kbyte
--	--

OB

<ul style="list-style-type: none"> • Number, max. • Size, max. • Number of free cycle OBs • Number of time alarm OBs • Number of delay alarm OBs • Number of cyclic interrupt OBs • Number of process alarm OBs • Number of startup OBs • Number of asynchronous error OBs • Number of synchronous error OBs 	see instruction list 64 kbyte 1; OB 1 1; OB 10 2; OB 20, 21 4; OB 32, 33, 34, 35 1; OB 40 1; OB 100 4; OB 80, 82, 85, 87 2; OB 121, 122
--	--

Nesting depth

<ul style="list-style-type: none"> • per priority class • additional within an error OB 	16 4
---	---------

Counters, timers and their retentivity

S7 counter

<ul style="list-style-type: none"> • Number 	256
--	-----

Retentivity

— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	Z 0 to Z 7

Counting range

— lower limit	0
— upper limit	999

IEC counter

<ul style="list-style-type: none"> • present • Type • Number 	Yes SFB Unlimited (limited only by RAM capacity)
---	--

S7 times

<ul style="list-style-type: none"> • Number 	256
--	-----

Retentivity

— adjustable	Yes
— lower limit	0
— upper limit	255
— preset	No retentivity

Time range

— lower limit	10 ms
— upper limit	9 990 s

IEC timer

<ul style="list-style-type: none"> • present • Type • Number 	Yes SFB Unlimited (limited only by RAM capacity)
---	--

Data areas and their retentivity

Retentive data area (incl. timers, counters, flags), max.	64 kbyte
---	----------

Flag

<ul style="list-style-type: none"> • Size, max. 	256 byte
--	----------

<ul style="list-style-type: none"> • Retentivity available • Retentivity preset • Number of clock memories 	Yes; MB 0 to MB 255 MB 0 to MB 15 8; 1 memory byte
Data blocks	
<ul style="list-style-type: none"> • Retentivity adjustable • Retentivity preset 	Yes; via non-retain property on DB Yes
Local data	
<ul style="list-style-type: none"> • per priority class, max. 	32 kbyte; Max. 2048 bytes per block
Address area	
I/O address area	
<ul style="list-style-type: none"> • Inputs • Outputs 	1 024 byte 1 024 byte
of which distributed	
<ul style="list-style-type: none"> — Inputs — Outputs 	none none
Process image	
<ul style="list-style-type: none"> • Inputs • Outputs • Inputs, adjustable • Outputs, adjustable • Inputs, default • Outputs, default 	1 024 byte 1 024 byte 1 024 byte 1 024 byte 128 byte 128 byte
Default addresses of the integrated channels	
<ul style="list-style-type: none"> — Digital inputs — Digital outputs 	124.0 to 125.1 124.0 to 124.5
Digital channels	
<ul style="list-style-type: none"> • Inputs <ul style="list-style-type: none"> — of which central • Outputs <ul style="list-style-type: none"> — of which central 	266 266 262 262
Analog channels	
<ul style="list-style-type: none"> • Inputs <ul style="list-style-type: none"> — of which central • Outputs <ul style="list-style-type: none"> — of which central 	64 64 64 64
Hardware configuration	
Number of expansion units, max.	0
Number of DP masters	
<ul style="list-style-type: none"> • integrated • via CP 	none 4
Number of operable FMs and CPs (recommended)	
<ul style="list-style-type: none"> • FM • CP, PtP • CP, LAN 	8 8 4
Rack	
<ul style="list-style-type: none"> • Racks, max. • Modules per rack, max. 	1 8
Time of day	
Clock	
<ul style="list-style-type: none"> • Software clock • retentive and synchronizable • Deviation per day, max. • Behavior of the clock following POWER-ON 	Yes No; Buffered: No, Can be synchronized: Yes 10 s; Typ.: 2 s the clock continues at the time of day it had when power was switched off
Operating hours counter	
<ul style="list-style-type: none"> • Number • Number/Number range • Range of values • Granularity • retentive 	1 0 0 to 2 ³¹ hours (when using SFC 101) 1 h Yes; Must be restarted at each restart
Clock synchronization	
<ul style="list-style-type: none"> • supported • to MPI, master 	Yes Yes

<ul style="list-style-type: none"> ● to MPI, slave 	Yes
<ul style="list-style-type: none"> ● in AS, master 	Yes
<ul style="list-style-type: none"> ● in AS, slave 	No
Digital inputs	
Number of digital inputs	10
<ul style="list-style-type: none"> ● of which inputs usable for technological functions integrated channels (DI) 	8
Input characteristic curve in accordance with IEC 61131, type 1	Yes
Number of simultaneously controllable inputs	
horizontal installation	
— up to 40 °C, max.	10
— up to 60 °C, max.	5
vertical installation	
— up to 40 °C, max.	5
Input voltage	
<ul style="list-style-type: none"> ● Rated value (DC) 	24 V
<ul style="list-style-type: none"> ● for signal "0" 	-3 to +5V
<ul style="list-style-type: none"> ● for signal "1" 	+15 to +30 V
Input current	
<ul style="list-style-type: none"> ● for signal "1", typ. 	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes; 0.1 / 0.3 / 3 / 15 ms (You can reconfigure the input delay of the standard inputs during program runtime. Please note that under certain circumstances your newly set filter time may not be effective until the next filter cycle.)
— Rated value	3 ms
for technological functions	
— at "0" to "1", max.	48 µs; Minimum pulse width/minimum pause between pulses at maximum counting frequency
Cable length	
<ul style="list-style-type: none"> ● shielded, max. 	1 000 m; 100 m for technological functions
<ul style="list-style-type: none"> ● unshielded, max. 	600 m; for technological functions: No
for technological functions	
— shielded, max.	100 m; at maximum count frequency
— unshielded, max.	not allowed
Digital outputs	
Number of digital outputs	6
<ul style="list-style-type: none"> ● of which high-speed outputs integrated channels (DO) 	2; Notice: You cannot connect the fast outputs of your CPU in parallel
Short-circuit protection	6
<ul style="list-style-type: none"> ● Response threshold, typ. 	Yes; Clocked electronically
Limitation of inductive shutdown voltage to	1 A
Controlling a digital input	L+ (-48 V)
Switching capacity of the outputs	
<ul style="list-style-type: none"> ● on lamp load, max. 	Yes
Load resistance range	
<ul style="list-style-type: none"> ● lower limit 	5 W
<ul style="list-style-type: none"> ● upper limit 	48 Ω
Output voltage	
<ul style="list-style-type: none"> ● for signal "1", min. 	4 kΩ
Output current	
<ul style="list-style-type: none"> ● for signal "1" rated value 	L+ (-0.8 V)
<ul style="list-style-type: none"> ● for signal "1" permissible range, min. 	500 mA
<ul style="list-style-type: none"> ● for signal "1" permissible range, max. 	5 mA
<ul style="list-style-type: none"> ● for signal "1" minimum load current 	0.6 A
<ul style="list-style-type: none"> ● for signal "0" residual current, max. 	5 mA
Parallel switching of two outputs	
<ul style="list-style-type: none"> ● for uprating 	0.5 mA
<ul style="list-style-type: none"> ● for redundant control of a load 	No
Switching frequency	
<ul style="list-style-type: none"> ● with resistive load, max. 	Yes
<ul style="list-style-type: none"> ● with inductive load, max. 	100 Hz
	0.5 Hz

<ul style="list-style-type: none"> • on lamp load, max. 	100 Hz
<ul style="list-style-type: none"> • of the pulse outputs, with resistive load, max. 	2.5 kHz
Total current of the outputs (per group)	
horizontal installation	
— up to 40 °C, max.	2 A
— up to 60 °C, max.	1.5 A
vertical installation	
— up to 40 °C, max.	1.5 A
Cable length	
<ul style="list-style-type: none"> • shielded, max. 	1 000 m
<ul style="list-style-type: none"> • unshielded, max. 	600 m
Analog inputs	
Number of analog inputs	0
integrated channels (AI)	0
Analog outputs	
Number of analog outputs	0
integrated channels (AO)	0
Encoder	
Connectable encoders	
<ul style="list-style-type: none"> • 2-wire sensor 	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interfaces	
Number of industrial Ethernet interfaces	0
Number of PROFINET interfaces	0
Number of RS 485 interfaces	1; MPI
Number of RS 422 interfaces	0
1. Interface	
Interface type	Integrated RS 485 interface
Isolated	No
Interface types	
<ul style="list-style-type: none"> • RS 485 	Yes
<ul style="list-style-type: none"> • Output current of the interface, max. 	200 mA
Protocols	
<ul style="list-style-type: none"> • MPI 	Yes
<ul style="list-style-type: none"> • PROFIBUS DP master 	No
<ul style="list-style-type: none"> • PROFIBUS DP slave 	No
<ul style="list-style-type: none"> • Point-to-point connection 	No
MPI	
<ul style="list-style-type: none"> • Transmission rate, max. 	187.5 kbit/s
Services	
— PG/OP communication	Yes
— Routing	No
— Global data communication	Yes
— S7 basic communication	Yes
— S7 communication	Yes; Only server, configured on one side
— S7 communication, as client	No; but via CP and loadable FB
— S7 communication, as server	Yes
Protocols	
PROFIsafe	No
communication functions / header	
PG/OP communication	Yes
Data record routing	No
Global data communication	
<ul style="list-style-type: none"> • supported 	Yes
<ul style="list-style-type: none"> • Number of GD loops, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, transmitter, max. 	8
<ul style="list-style-type: none"> • Number of GD packets, receiver, max. 	8
<ul style="list-style-type: none"> • Size of GD packets, max. 	22 byte
<ul style="list-style-type: none"> • Size of GD packet (of which consistent), max. 	22 byte
S7 basic communication	

<ul style="list-style-type: none"> • supported • User data per job, max. • User data per job (of which consistent), max. 	Yes 76 byte 76 byte; 76 bytes (with X_SEND or X_RCV); 64 bytes (with X_PUT or X_GET as server)
S7 communication	
<ul style="list-style-type: none"> • supported • as server • as client • User data per job, max. • User data per job (of which consistent), max. 	Yes Yes Yes; Via CP and loadable FB 180 byte; (with PUT/GET) 240 byte; as server
S5 compatible communication	
<ul style="list-style-type: none"> • supported 	Yes; via CP and loadable FC
Number of connections	
<ul style="list-style-type: none"> • overall • usable for PG communication <ul style="list-style-type: none"> — reserved for PG communication — adjustable for PG communication, min. — adjustable for PG communication, max. • usable for OP communication <ul style="list-style-type: none"> — reserved for OP communication — adjustable for OP communication, min. — adjustable for OP communication, max. • usable for S7 basic communication <ul style="list-style-type: none"> — reserved for S7 basic communication — adjustable for S7 basic communication, min. — adjustable for S7 basic communication, max. 	6 5 1 1 5 5 1 1 5 2 0 0 2
S7 message functions	
Number of login stations for message functions, max.	6; Depending on the configured connections for PG/OP and S7 basic communication
Process diagnostic messages	Yes
simultaneously active Alarm-S blocks, max.	300
Test commissioning functions	
Status block	Yes; Up to 2 simultaneously
Single step	Yes
Number of breakpoints	4
Status/control	
<ul style="list-style-type: none"> • Status/control variable • Variables • Number of variables, max. <ul style="list-style-type: none"> — of which status variables, max. — of which control variables, max. 	Yes Inputs, outputs, memory bits, DB, times, counters 30 30 14
Forcing	
<ul style="list-style-type: none"> • Forcing • Forcing, variables • Number of variables, max. 	Yes Inputs, outputs 10
Diagnostic buffer	
<ul style="list-style-type: none"> • present • Number of entries, max. <ul style="list-style-type: none"> — adjustable — of which powerfail-proof • Number of entries readable in RUN, max. <ul style="list-style-type: none"> — adjustable — preset 	Yes 500 No 100; Only the last 100 entries are retained 499 Yes; From 10 to 499 10
Service data	
<ul style="list-style-type: none"> • can be read out 	Yes
Interrupts/diagnostics/status information	
Diagnostics indication LED	
<ul style="list-style-type: none"> • Status indicator digital input (green) • Status indicator digital output (green) 	Yes Yes
Integrated Functions	
Frequency measurement	Yes
<ul style="list-style-type: none"> • Number of frequency meters 	2; up to 10 kHz (see "Technological Functions" manual)
controlled positioning	No

integrated function blocks (closed-loop control)	No
PID controller	No
Number of pulse outputs	2; Pulse width modulation up to 2.5 kHz (see "Technological Functions" Manual)
Limit frequency (pulse)	2.5 kHz
Potential separation	
Potential separation digital inputs	
• Potential separation digital inputs	Yes
• between the channels	No
• between the channels and backplane bus	Yes
Potential separation digital outputs	
• Potential separation digital outputs	Yes
• between the channels	No
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	600 V DC
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
configuration / header	
Configuration software	
• STEP 7	Yes; STEP 7 V5.5 + SP1 or higher or STEP 7 V5.3 + SP2 or higher with HSP 203
• STEP 7 Lite	No
configuration / programming / header	
• Command set	see instruction list
• Nesting levels	8
• System functions (SFC)	see instruction list
• System function blocks (SFB)	see instruction list
Programming language	
— LAD	Yes
— FBD	Yes
— STL	Yes
— SCL	Yes
— GRAPH	Yes
— HiGraph®	Yes
Know-how protection	
• User program protection/password protection	Yes
• Block encryption	Yes; With S7 block Privacy
Dimensions	
Width	80 mm
Height	125 mm
Depth	130 mm
Weights	
Weight, approx.	410 g
last modified:	7/28/2021 